

## TECHNICAL INFORMATION SHEET

### QuickPrime™ Plus LVOC

**Item Description**

3-gallon (11.4 L) pail  
1-gallon (3.78 L) pail  
Quart (0.946 L) pail

**Item Number**

W563587043  
W563587045  
W56RAC1697



### Product Information

#### Description:

QuickPrime Plus LVOC is designed to clean and prime RubberGard™ EPDM membrane and RubberGard EcoWhite™ EPDM prior to application of QuickSeam™ products where required by Firestone Specifications and Details.

QuickPrime Plus LVOC must be applied with a QuickScrubber™ or QuickScrubber Plus pad and handle when preparing RubberGard membrane to receive QuickSeam Tape products. It may also be used to clean membrane prior to the application of Firestone Lap Sealant LVOC.

#### Method of Application:

1. Splice surfaces must be clean, dry, and free of foreign materials and excess dusting agent. Clean with broom or rags to remove contaminants.
2. Stir QuickSeam Plus LVOC thoroughly before and during use. Apply QuickPrime Plus LVOC using the QuickScrubber or QuickScrubber Plus pad and handle.
3. Use back and forth strokes with heavy pressure along the length of the splicing area, until membrane surfaces become black in color with no streaking or puddling.
4. Allow the QuickPrime Plus LVOC surfaces to flash off completely according to the touch-push test (usually less than 30 minutes) before applying QuickSeam products or Lap Sealant LVOC.
5. Complete QuickSeam product installation or Lap Sealant LVOC application in accordance with Firestone Specifications and Details.

#### Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.
- Shelf life of one year can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

#### Coverage Rate:

150-225 ft² per gal (3.68-5.52 sq m/l) for a one side application.

# TECHNICAL INFORMATION SHEET

## QuickPrime™ Plus LVOC

### Precautions:

- Thinning is not allowed.
- Flammable. Keep away from fires (open flame) and other possible ignition sources during storage and use. Do not smoke when using.
- Use only in well-ventilated areas.
- Use of neoprene or nitrile gloves and eye protection with side shield is recommended.
- Use only in conjunction with QuickScrubber or QuickScrubber Plus. Do not apply with rollers, brushes or rags.
- Mix thoroughly before and during use.
- Refer to Safety Data Sheet (SDS).

### LEED® Information:

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: South Bend, IN

\*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.



### Typical Properties

Property	Value
Base	Synthetic Rubber Polymers
Color	Black
Solvents	Hydrocarbon and Halogenated Solvents
Percent Solids	8.5-10.5%
Viscosity	Very thin, free flowing
Weight (Nominal)	9.55 lb/gal (1.14 kg/L)
Specific Gravity	1.146
Flash Point	57.2 °F (14 °C)
V.O.C. Content	Not to exceed 2.1 lb/gal (250 g/L)

### Packaging

Container	Pallet
3-gal (11.4 L) pail	75, 3 gal pails
1-gal (3.78 L) can, 4/case	54 cases
Quart (0.946 L) can, 12/carton	50 cartons

Please contact Firestone Technical Services Department at 1-800-428-4511 for further information.

*This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.*